

MODEL	PART #	LENGTH in/cm	WIDTH in/cm	HEIGHT in/cm	Overall Height	WEIGHT lbs/kg	HEAT	CAPACITY gal/liter	HERD CAPACITY
WaterMaster									
WM 1200	18053	144/366	24/61	24/61	28.5/72	250/113	CF Opt/Opt Imm & Self Reg Heat Cbl	60/227	500 beef, 250 dairy
WM 96	18007	96/244	33/84	22/56	28/71	200/91	CF Std/Opt Imm & Self Reg Heat Cbl	75/284	300 beef, 150 dairy
WM 90	16467	90/229	33/85	22/56	28/71	180/82	CF Std/Opt Imm & Self Reg Heat Cbl	30/114	300 beef, 150 dairy
WM 600	18171	72/183	24/61	24/61	28.5/72	140/64	CF Opt/Opt Imm & Self Reg Heat Cbl	28/106	250 beef, 125 dairy
WM 54	16542	54/137	33/87	22/56	28/71	125/57	CF Std/Opt Imm & Self Reg Heat Cbl	18/68	200 beef, 100 dairy
Deep 54	18355	54/137	33/84	28/71	22/56	125/57	CF Std/Opt Imm & Self Reg Heat Cbl	54/204	200 beef, 100 dairy
WaterMatic									
1000	18110	42/107	42/107	26/66	32/81	120/54	Opt Imm & Self Reg Heat Cbl	22/83	275 beef, 135 dairy
300	18050	36/91	21.5/55	26/66	31/79	69/31	Opt Imm & Self Reg Heat Cbl	8.2/31	125 beef, 60 dairy
150S	18222	33.5/85	14/36	13/33	22.5/57	39/18	Opt Imm & Self Reg Heat Cbl	4.2/16	100 sheep or goats
150	18166	33.5/85	14/36	18/46	23.5/60	47/21	Opt Imm & Self Reg Heat Cbl	4.2/16	40 beef, 40 horses
100	18165	24.5/62	14/36	18/46	23.5/60	36/16	Opt Imm & Self Reg Heat Cbl	2.8/11	20 beef, 20 horses
Thrifty King									
CT6	16440	72.5/184	39/99	19/48	25/64	210/95	Opt Imm & Self Reg Heat Cbl	55/208	300 beef
CT4-2000	16430	42.8/109	35/89	19/48	25/64	152/69	Opt Imm & Self Reg Heat Cbl	45.5/172	200 beef
CT2-2000	16299	42.8/109	24/61	19/48	25/64	90/41	Opt Imm & Self Reg Heat Cbl	28/106	100 beef
CT1-2000	16271	28/71	20.3/51	19/48	25/64	53/24	Opt Imm & Self Reg Heat Cbl	11.2/42	30 beef
OmniFount									
MODEL	PART #	LENGTH in/cm	WIDTH in/cm	HEIGHT in/cm	Overall Height	WEIGHT lbs/kg	HEAT	CAPACITY gal/liter	HERD CAPACITY
Omni 10 240V	18461	40.5/103	40.5/103	31.5/80	26/66	150/68	Std Elec or CF 948W (4.0A@240V)	28/106	275 beef, 135 dairy
Omni 5 240V	16829	40/102	23.5/60	26/66	26/66	88/40	Standard Electric 648W (2.7A@240V)	16/61	150 beef, 75 dairy
Omni 3 240V	18273	31.5/80	22/56	26/66	26/66	75/34	Standard Electric 648W (2.7A@240V)	10./38	100 beef, 50 dairy
Omni 2 240V	16844	28.3/72	14.5/37	18/46	26/66	45/20	Standard Electric 448W (1.9A@240V)	2.2/8	40 horses, 40 beef
Omni 1 240V	18362	20/51	14.5/37	18/46	26/66	39/18	Standard Electric 248W (1.0A@240V)	1.5/6	20 Horses or beef
EcoFounts NEW									
Eco 1	18430	22/55.9	18/45.7	20/51	20/51	41/18.60	Standard Electric 248W (1.0A@240V)	3.5/13	30 beef or horses
Eco 2	18440	36/91.4	18.5/47	20/51	20/51	75/34.02	Standard Electric 448W (1.9A@240V)	6.5/25	60 beef or horses
CattleMaster									
CM 1440 240V	18255	145.5/370	23.5/59.7	16/41	26/66	272/123	Std Elec or CF 948W (4.0A@240V)	60/227	475 beef, 240 dairy
CM 840 240V	18243	87/221	23.5/59.7	16/41	26/66	130/64	Std Elec or CF 948W (4.0A@240V)	35/133	300 beef, 150 dairy
CM 480 240V	18251	51/129.5	23.5/59.7	16/41	26/66	90/41	Std Elec or Cf 648W (2.7A@240V)	20/76	200 beef, 100 dairy
Cattle Fountain									
5E 240V	16824	38.4/98	20.1/51	26/66	30/76	101/46	Std Elec or Cf 648W (2.7A@240V)	16/61	150 beef, 75 dairy
3E 240V	16826	29.6/75	18/46	26/66	30/76	82/37	Std Elec or Cf 648W (2.7A@240V)	10/38	100 beef, 50 dairy
Combination Fountain									
3 Combo. 240V	16816	29.6/75	18/46	26/66	30/76	100/45	Std Elec or CF 948W (4.0A@240V)	10/38	100 beef, 80 hogs
AC Series									
MODEL	PART #	LENGTH in/cm	WIDTH in/cm	HEIGHT in/cm	Overall Height	WEIGHT lbs/kg	HEAT	CAPACITY gal/liter	HERD CAPACITY
2AC 240V	16839	25.9/66	11.4/29	17.8/45	21.5/55	38/17	Standard Electric 448W (1.9A@240V)	2.2/8	40 beef, 80 calves
1AC 240V	16841	17.6/45	11.4/29	17.8/45	21.5/55	28/13	Standard Electric 448W (1.5A@240V)	1.5/6	20 beef, 40 calves
AC Special 240	18383	25.9/66	11.4/29	10.8/27	14.5/37	30/14	Standard Electric 448W (1.9A@240V)	2.2/8	40 beef, 80 calves
Commander Series									
Comm. 2 240V	16820	32.7/83	17/43	16/41	16/41	68/31	Standard Electric 448W (1.9A@240V)	6.5/25	60 beef
Comm. 1 240V	16751	20.1/51	17/43	16/41	16/41	41/19	Standard Electric 248W (1.0A@240V)	3.5/13	30 beef
Stall Fount									
Stall Fount 125 240V	18415	14/36	13/33	Adjust.	Adjust.	31/14	Standard Electric 248W (1.03A@240V)	1.9/7	single stall
Stall Fount	16871	14/36	13/33	Adjust.	Adjust.	13/6	NA	1.9/7	single stall
Shroud Set	18092	19.4/49 each	13/34	Up to 4'		16/7	NA	NA	NA
Pork King									
PK 4 240V	16845	31.5/80	23.3/59	7in/18cm	12.5/32	63/29	Standard Electric 848W (3.5A@240V)	3.5/13	160 hogs
PK 2-1 240V	16846	23.2/59	23.3/59	7in/18cm	12.5/32	50/23	Standard Electric 448W (1.9A@240V)	2/8	80 hogs
PK 2 240V	16847	31.5/80	13/33	7in/18cm	12.5/32	42/19	Standard Electric 448W (1.9A@240V)	2/8	80 hogs
PK 1 240V	16848	23.2/59	13/33	7in/18cm	12.5/32	30/14	Standard Electric 448W (1.5A@240V)	1.2/5	40 hogs
Thrifty King for Swine									
HG 4	16260	31.3/80	31.3/80	8in/20cm	16/41	70/32	Opt Imm & Self Reg Heat Cbl	5.2/20	160 hogs

HG 2	16259	31.3/80	20/51	8in/20cm	16/41	50/23	Opt Imm & Self Reg Heat Cbl	2/8	80 hogs
------	-------	---------	-------	----------	-------	-------	-----------------------------	-----	---------

